K-ACS-2 Armored Cable Slitter

The small-cable armored slitter — red roller, 4 to 10 mm, the same guided blade in a body sized for micro and branch cables.

Small armored cables — the 4 to 10 mm micro and branch constructions — are built like their big brothers in miniature: jacket, corrugated armor, and a tube with very little wall to spare. A full-size slitter's roller cannot seat them. The K-ACS-2's red roller is grooved for the small range, and that groove is what holds the blade line true while the depth dial keeps the cut out of the tube.



K-ACS-2 — hook body, red guide roller and tension knob

Key Features

- Red roller, small-cable range: cables from 4 to 10 mm — armored micro cables and small branch and drop constructions that a full-size roller cannot sit on or steer
- Jacket and armor in one pass: the hardened alloy steel blade scores the polyethylene jacket and the corrugated copper, steel or aluminium armor together in a single draw
- Depth set to the cable, not guessed: the dial in the butt of the handle drives the blade in or out, to 5.5 mm maximum — on a thin small-cable jacket, that control keeps the blade out of the tube
- Slit or ring with one lever: flip the blade 90° between a lengthwise slit and a circumferential ring cut — the two moves of mid-span work, without changing tools
- A matched pair on the truck: the same cast body, knurled barrel handle and stored hex key as the 8–28.6 mm K-ACS — told apart at a glance by the roller colour
- Private labeling made to your requirements — labels with your logo, part numbers and barcodes on the inner boxes and outer cartons, ready for your warehouse

Specifications

Cable diameter	4–10 mm
Guide roller	Red anodised aluminium roller
Blade	Hardened alloy steel, replaceable
Blade depth	Adjustable to 5.5 mm maximum
Cutting modes	Longitudinal slit and circumferential ring cut — blade rotates 90° on its lever
Body	Anodised aluminium and steel, single handle
Dimensions	127 mm (overall length)
Weight	284 g

Two More Views

The side profile shows the same hook, throat and barrel handle as the full-size model — only the roller is sized down. From the top, the red roller's grooved face is the range code itself: red for 4–10 mm cables, gold for 8–28.6 mm, picked at a glance in the kit.



Side view — hook profile and red roller



Top view — the red guide roller

In Use

Seat the cable in the hook and bring the red roller down with the tension knob until its groove centres the cable under the blade. Set the blade depth shallow on the butt dial — small-cable jackets are thin — and prove it on a scrap end: armor parted, tube unmarked. Draw to slit; flip the lever to ring. For a mid-span window on a live branch cable, ring at both ends, slit between the rings and lift the shell. Cables over 10 mm will not seat in this roller — step up to the gold-roller models rather than forcing the head down.

OEM & Private Label

The K-ACS-2 is supplied in neutral, unbranded stock as standard. Private labeling is made to your requirements — labels with your logo, part numbers and barcodes on the tools, the inner boxes and the outer cartons, so the goods arrive ready for your warehouse. Custom barcode & contract labeling is applied to every inner box and outer carton to your receiving specification.